



16-PORT PoE+ Managed Switch


NV-116S/P+



KEY FEATURES

- 16 x 100Mb/s PoE+
- 2 x 1000Mb/s UPLINK, 2 x 1000Mb/s SFP UPLINK

DIMENSIONS



GENERAL	
Device Type	PoE+ Managed Switch
NETWORK	
Ports	PoE Ports: 16 x 10Mb/s / 100Mb/s UPLINK ports: 4 x 10Mb/s / 100Mb/s / 1Gb/s
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
Protocols Support	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3z 1000BASE-SX/LX
QoS support	yes
FUNCTIONS	
Buttons	1 button to device reset
Surge protection	yes
INSTALLATION PARAMETERS	
RACK Mount 19"	1U
Dimensions (mm)	315 (W) x 44 (H) x 442 (L)
Weight	3.54 kg
Input Voltage	100 ~ 240 VAC, 50/60Hz
Power Consumption	320 W (maximum)
PoE Budget	250 W for ports 1 to 16, up to 30 W for one port
Operating Temperature	0°C ~ 55°C