



# 24-PORT POE+ Managed Switch


NV-124S/P+



## KEY FEATURES

- 24 x 100Mb/s PoE+
- 2 x 1000Mb/s UPLINK, 2 x 1000Mb/s SFP UPLINK

## DIMENSIONS



GENERAL	
Device Type	PoE+ Managed Switch
NETWORK	
Ports	PoE Ports: 24 x 10Mb/s / 100Mb/s UPLINK ports: 2 x 10Mb/s / 100Mb/s / 1Gb/s, Optical UPLINK ports: 2 x SFP
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
Protocols Support	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3z 1000BASE-SX/LX
QoS support	yes
FUNCTIONS	
Buttons	1 button to device reset
Surge protection	yes
INSTALLATION PARAMETERS	
RACK Mount 19"	1U
Dimensions (mm)	315 (W) x 44 (H) x 442 (L)
Weight	3.73 kg
Input Voltage	100 ~ 240 VAC, 50/60Hz
Power Consumption	420 W (maximum)
PoE Budget	370 W for ports 1 to 24, up to 30 W for one port
Operating Temperature	0°C ~ 55°C