

NOVUS MANAGEMENT SYSTEM VSS Client Station

NMS VSS CLIENT 7-T-III



FUNCTIONS









COMPATIBILITY



KEY FEATURES

- •Monitoring of up to 70 channels
- •Supports resolution up to 4000 x 3000
- •Supports up to 6 monitors simultaneously
- •Operating system: Microsoft Windows 10 IoT •Recording and surveillance system: NOVUS
- MANAGEMENT SYSTEM VSS
- . Compatible with NOVUS recorders

DIMENSIONS









Video	
Tideo	
IP Cameras	up to 70 channels at 640×480 resolution resolution using H.264 codec (video + audio) up to 55 channels at 640×480 resolution resolution using H.265 codec (video + audio)
Maximum Supported Camera Resolution	4000 x 3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Protocols	Novus, ONVIF, RTSP (purchase of the appropriate license is required)
Dualstreaming Support	yes
Display	
Monitor Output	2 x HDMI 2.0b, 2 x Display Port 1.4, 2 x Dual link DVI-D, (up to 6 monitors simultaneously)
Maximum Resolution	6 x 4K UltraHD
Audio	
Audio input	1 x Line in (3,5mm), 1 x Mic in(3,5mm)
Audio Output	1 x Line output (3,5mm), 2 x HDMI, 2 x Display Port
Performance - H.264	
2MPX IP Camera	Display up to: 70 sub streams or 20 main streams Playback up to: 20 main streams
4MPX IP Camera	Display up to: 70 sub streams or 13 main streams Playback up to: 13 main streams
5MPX IP Camera	Display up to: 60 sub streams or 8 main streams Playback up to: 8 main streams
8MPX IP Camera	Display up to: 40 sub streams or 5 main streams Playback up to: 5 main streams
12MPX IP Camera	Display up to: 35 sub streams or 4 main streams Playback up to: 4 main streams
Performance - H.265	
2MPX IP Camera	Display up to: 55 sub streams or 15 main streams Playback up to: 15 main streams
4MPX IP Camera	Display up to: 50 sub streams or 8 main streams Playback up to: 8 main streams
5MPX IP Camera	Display up to: 60 sub streams or 5 main streams Playback up to: 5 main streams
8MPX IP Camera	Display up to: 65 sub streams or 4 main streams Playback up to: 4 main streams
12MPX IP Camera	Display up to: 32 sub streams or 4 main streams

Bandwidth 350 Mb/s in total from all NVRs HTTP, TCP/IP, IPv4/v6, UDP, FTP, DHCP, DNS, NTP, RTSP, UPnP, SMTP Network Protocols Support PTZ

USB port (HDD or Flash memory), network

1 x Ethernet - RJ-45 interface, 10/100/1000/2500 Mbit/s

built-in: 1 x SSD NVMe

PTZ Functions Auxiliary Interfaces 4 x USB 2.0, 4 x USB 3.2, 1 x USB 3.2 Type-C

Operating system Recording and Surveillance System NOVUS MANAGEMENT SYSTEM VSS Operation Mode triplex

Control PC mouse and keyboard (in-set included), DCZ keyboard System Diagnostic automatic control of: HDDs, network, camera connection loss password protection, IP filtering, limiting the number of connections

177 (W) x 483 (H) x 505 (D) Weight 10 kg built-in PSU 230 VAC/700 W Power Supply/Power Consumption 350W/280W (without HDD for recording)

Operating Temperature

Note: The device requires registration and license activation. There is an option to activate a 60-day trial lice application is required. To choose the appropriate license, please contact the sales department. The device may be available in another housing variant, with dimensions 185 (W) \times 412 (H) \times 450 (D). After this period, the purchase of a NOVUS MANAGEMENT SYSTEM VSS software license sp

5°C ~ 35°C