



High-Speed Dome IP Camera with Face Recognition, License Plate Recognition and Object Tracking

NVIP-5SD-4550/33/F



FUNCTIONS



The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

COMPATIBILITY



KEY FEATURES

- Resolution: 5 MPX
- Lens: motorized varifocal, AI and AF function, optical zoom 33x, f=4.3 ~ 142 mm/F1.6 ~ 4.3
- D/N function - IR cut filter
- Auto Tracking
- Video content analysis based on Deep Learning
- Licence plate recognition (LPR)
- microSD card support
- WDR with double scan sensor
- two-way audio
- Min. Illumination from 0.003 lx (0 lx, IR on)
- IR LED, range up to 150 m (depends on current optical zoom value)

DIMENSIONS

Image	
Image Sensor	5 MPX CMOS sensor 1/2.7" OmniVision
Number of Effective Pixels	2688 (H) x 1944 (V)
Min. Illumination	0.003 lx/F1.6 - color mode, 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s – 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Digital zoom	16x
Lens	
Optical Zoom	33x
Lens Type	motorized, auto-iris function, f=4.3 ~ 142 mm/F1.6 ~ F4.3
Auto-focus	zoom trigger, day/night mode trigger, manual trigger
DORI	
DORI (Detection, Observation, Recognition, Identification)	for f = 4.3mm - D: 86m, O: 34.4m, R: 17m, I: 8.6m for f = 142mm - D: 2840m, O: 1136m, R: 568m, I: 284m
Day/Night	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Visible Light Sensor	yes
Network	
Stream Resolution	2592 x 1520, 2592 x 1944, 2304 x 1296, 1920 x 1080 (Full HD), 2048 x 1536 (QXGA), 1280 x 960, 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3 (main stream, sub stream, third stream)
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711
Number of Simultaneous Connections	max. 3 connections, (max. 14 streams in total)
Bandwidth	40 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4/IPv6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, PPPoE, SMTP, HTML5, RTMP
ONVIF Protocol Support	Profile G/S/T/M
Camera Configuration	from Edge, Firefox, Chrome, Opera browser languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 4000
Mobile applications	RxCamView (iPhone, Android)
PTZ	
Preset Commands	255
Tours	4 (up to 32 presets per tour)
Patterns	4 (max. 512 commands for each pattern)
Tilt/Pan Range	-10° ~ 90°/360° (continuous)
Pan/Tilt Speed	up to 200°/s (proportional to zoom)
Preset Speed	up to 200°/s
Video Analytics	
Functions	auto tracking linked to Video Content Analysis (VCA) functions, tamper, abandoned object, object disappearance, line cross, zone entrance, zone exit, zone violation, multi loiter, cross counting, heat map, queue length detection, objects distinguishing, comparing faces, smart motion detection with objects distinguishing
Other functions	
Security	video encryption, IEEE 802.1X support, HTTPS support, MAC/IP address filtering, force change of default password
Privacy Zones	6 video mask type: single color
Motion Detection	yes
Audio Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Prealarm/Postalarm	up to 6 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation, HTTP notification, object tracking
Restoring default settings	via web browser, using reset button
Licence plate recognition (LPR)	
Autonomous operation mode	yes - recognition function implemented in the camera
Capacity of License Plate Database	up to 10000 license plates, on all lists.



207 mm



374 mm

398 mm

Types of recognized number plates	all countries of the European Union
Barrier control	yes - built-in relay output
Recommended maximum speed of the vehicle	up to 60 km/h
Data recorded in the camera base	number of recognised licence plate
Reactions for the licence plate recognition	e-mail with attachment, saving file on FTP server, alarm output activation
IR LED	
LED Number	10
Range	up to 150 m (depends on current optical zoom value)
Smart IR	yes (hardware support)
Interfaces	
Video Output	BNC, 1.0 Vp-p, 75 Ohm
Audio Input/Output	1/1
Alarm Input/Output	1 (NO/NC)/1 relay type (max. 12VDC/300mA)
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
Installation parameters	
Dimensions (mm)	207 (Ø) x 329 (H) with bracket: 207 (W) x 398 (H) x 374 (L)
Weight	3.7 kg with bracket: 4.7 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, In set: outdoor housing (integrated with the camera), wall mount bracket
Power Supply	12 VDC, PoE+ (IEEE 802.3at, Klasa 4)
Power Consumption	14 W, 25 W (IR illuminator on)
Operating Temperature	-30°C ~ 60°C
Cold start temperature	-35°C
Humidity	max. 90%, relative (non-condensing)

The camera has the ability to autonomously recognize and compare faces, but it can also be part of the face recognition system, working with selected NOVUS 4000 series IP recorders (models with "F" in the name).