

NOVUS

Dome AHD Camera

NVAHD-2DN5102D/IR-1

5000
AHD SERIES



FUNCTIONS



KEY FEATURES

- D/N function - IR cut filter
- resolution 1080p
- Lens: varifocal, f=2.8 ~ 12 mm/F1.2
- Smart IR function
- Extended IR LED life
- optional UTC remote controller
- Min. Illumination from 0.0001 lx (0 lx, IR on)
- IR LED, range up to 15 m

DIMENSIONS



Image	
Image Sensor	CMOS sensor 1/2.9" SONY
Operating mode	AHD 1080p, analog 960H
Number of Effective Pixels	1920 (H) x 1080 (V)
Resolution	1080p
Min. Illumination	0.5 lx/F1.2 - color mode, 0.01 lx/F1.2 - B/W mode, 0.001 lx/F1.2 - color mode (DSS), 0.0001 lx/F1.2 - B/W mode (DSS), 0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s (AHD), , 1/50 s ~ 1/50000 s (analog 960H)
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Lens	
Lens Type	varifocal, f=2.8 ~ 12 mm/F1.2
Day/Night	
Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 60 s
Visible Light Sensor	yes
Other functions	
OSD	languages: Polish, English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Remote control	Yes (optional UTC remote control)*
IR LED	
LED Number	24
Range	15 m
Angle	120°
Interfaces	
Video Output	BNC, 1.0 Vp-p, 75 Ohm
Installation parameters	
Dimensions (mm)	112 (Ø) x 87 (H)
Weight	0.17 kg
Enclosure	plastic, white
Power Supply	12 VDC
Power Consumption	1 W, 2.7 W (IR illuminator on)
Operating Temperature	-30°C ~ 40°C

* Note: UTC functionality available on cameras with serial numbers starting from: 150611xxxx
Remote controller type: NV-RCUTC-35HD