

NOVUS

Bullet IP Camera

NVIP-1DN5001H/IRH-1P



5000
IP SERIES

FUNCTIONS



COMPLIANCE



KEY FEATURES

- Resolution: 1.3 MPX
- Lens: fixed focal, f=3.6 mm/F2.2
- D/N function - IR cut filter
- Min. Illumination from 0.034 lx (0 lx, IR on)
- IR LED, range up to 15 m

DIMENSIONS




Image	
Image Sensor	1.3 MPX CMOS sensor 1/3" APTINA
Number of Effective Pixels	1280 (H) x 960 (V)
Min. Illumination	0.67 lx/F2.2 - color mode, 0.034 lx/F2.2 - color mode (DSS), 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/50000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Digital Noise Reduction (DNR)	3D
Lens	
Lens Type	fixed focal, f=3.6 mm/F2.2
Day/Night	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Delay	0 ~ 180 s
Switching Schedule	yes
Visible Light Sensor	yes
Network	
Stream Resolution	1280 x 960, 1280 x 720 (HD), 720 x 576 (D1), 640 x 480 (VGA), 640 x 360, 352 x 288 (CIF), 320 x 240 (QVGA)
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 2
Video/Audio Compression	H.264, MJPEG/-
Number of Simultaneous Connections	max. 10
Bandwidth	3.5 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, IPv6, FTP, DHCP, DNS, 3GPP, SMTP
ONVIF Protocol Support	Profile S (ONVIF2.2)
Camera Configuration	from Internet Explorer, Firefox, Chrome, Opera browser languages: Polish, English, Russian
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS
Other functions	
Privacy Zones	5
Motion Detection	yes
Image Processing	180° image rotation, mirror effect
Prealarm/Postalarm	up to 5 MB/up to 86400 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on NAS server
IR LED	
LED Number	2
Range	15 m
Angle	90°
Interfaces	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Installation parameters	
Dimensions (mm)	with bracket: 70 (W) x 63 (H) x 169 (L)
Weight	0.473 kg
Degree of Protection	IP 66 (details in the user's manual)
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Power Consumption	3.5 W, 6 W (IR illuminator on), 6.5 W (heater on), 8.5 W (IR and heater on)
Operating Temperature	-40°C ~ 55°C
Built-in Heater/Fan	yes/no