



Hardened 8-port PoE+ Switch

NVS-3208SP-EH



KEY FEATURES

- 8 x 100Mb/s PoE+
- 2 x 1000Mb/s SFP UPLINK
- Operating temperature: -40°C + 70°C

DIMENSIONS



162 mm

45 mm



110 mm



GENERAL	
Device Type	Hardened PoE+ switch
NETWORK	
Ports	PoE+ Ports: 8 x 10Mb/s / 100Mb/s (the number of ports simultaneously operating with PoE+ mode is limited by PoE budget), Optical UPLINK ports: 2 x SFP
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
PoE modes	Endspan (1,2+ / 3,6-)
Switching capacity	5.6 Gb/s
Protocols Support	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3x
MAC ADDRESS list	4K
INSTALLATION PARAMETERS	
Case	Metal, color navy blue, enclosure with possibility to mount on DIN TH35 rail
Dimensions (mm)	162 (W) x 110 (H) x 45 (L)
Weight	0.7 g
Input Voltage	48 VDC (power supply 100 ~ 240 VAC/48 VDC included)
Power Consumption	144 W (maximum)
PoE Budget	130 W for ports 1 to 8, up to 30 W for one port
Operating Temperature	-40°C ~ 70°C