



4-port PoE+ Switch

NVS-3304SP




KEY FEATURES

- 4 x 100Mb/s PoE+
- 2 x 100Mb/s UPLINK

DIMENSIONS



22 mm



75 mm

102 mm

GENERAL	
Device Type	PoE+ Switch
NETWORK	
Ports	PoE+ Ports: 4 x 10Mb/s / 100Mb/s (the number of ports simultaneously operating with PoE + mode is limited by PoE budget), UPLINK ports: 2 x 10Mb/s / 100Mb/s
PoE standards	IEEE802.3af, Class 3, IEEE802.3at, Class 4
PoE modes	Endspan (1,2+ / 3,6-)
Switching capacity	1.2 Gb/s
Protocols Support	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX
MAC ADDRESS list	1K
FUNCTIONS	
CCTV	Extended mode switch that increases the data and power transmission distance up to 200m (Using 10 Mb/s bandwidth)
Additional operating modes	Extended
Surge protection	yes
INSTALLATION PARAMETERS	
Case	Metal, color navy blue
Dimensions (mm)	102 (W) x 22 (H) x 75 (L)
Weight	0.3 g
Input Voltage	53 VDC (power supply 100 ~ 240 VAC/53 VDC included)
Power Consumption	60 W (maximum)
PoE Budget	55 W for ports 1 to 4, up to 30 W for one port
Operating Temperature	0°C ~ 40°C
Humidity	0~85% (relative, non-condensing)

Maximum ranges depend on cable quality, interference and camera model. The ranges were determined in laboratory conditions. For information on the exact ranges for a given camera connection and switches please contact support or perform tests in the real environment of the future operation of the devices.