



24-port PoE+ Managed Switch


NVS-5124SP



KEY FEATURES

- 24 x 100Mb/s PoE+
- 2 x 1000Mb/s UPLINK, 4 x 1000Mb/s SFP UPLINK
- Operating temperature: 0°C ÷ 40°C

DIMENSIONS



| GENERAL | |
|-----------------------------|---|
| Device Type | PoE+ Managed Switch |
| NETWORK | |
| Ports | PoE+ Ports: 24 x 10Mb/s / 100Mb/s (the number of ports simultaneously operating with PoE + mode is limited by PoE budget), UPLINK SFP port 1Gb/s x 2, Uplink Combo x 2 :SFP(1Gb/s) + RJ45(1Gb/s) |
| PoE standards | IEEE802.3af, Class 3, IEEE802.3at, Class 4 |
| PoE modes | Endspan (1,2+ / 3,6-) |
| Switching capacity | 12.8 Gb/s |
| Protocols Support | IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-T, IEEE 802.3z 1000BASE-SX/LX, IEEE 802.3x, IEEE 802.1p CoS, IEEE 802.1D spanning tree protocol, IEEE 802.1s multiple tree protocol, IEEE 802.1ad LACP aggregation, IEEE 802.1Q VLAN tagging |
| Additional network features | VLAN, IGMP snooping, bandwidth management |
| QoS support | yes |
| CoS support | yes |
| Jumbo frame (bytes) | 2K |
| MAC ADDRESS list | 8K |
| FUNCTIONS | |
| Buttons | 1 button to device reset |
| Surge protection | yes |
| INSTALLATION PARAMETERS | |
| RACK Mount 19" | 1U |
| Case | Metal, color navy blue |
| Dimensions (mm) | 200 (W) x 44 (H) x 440 (L) |
| Weight | 3.2 kg |
| Input Voltage | 100 ~ 240 VAC, 50/60Hz |
| Power Consumption | 400 W (maximum) |
| PoE Budget | 370 W for ports 1 to 24, up to 30 W for one port |
| Operating Temperature | 0°C ~ 40°C |

The values was achieved in a test environment. In different environment this value can change due to interferences or influence of other devices.