# IP user monitor

NVE-M200WIFI




The **NVE-M200** IP user monitor is an elegant and aesthetically made device designed for installation in a residential or office space. The large color screen and intuitive menu allows quick and convenient use of its functions. In addition to the basic functions (camera image display, door opening), the on-screen menu also allows you to view and delete messages and photos. The device's basic memory allows you to save up to 100 photos or 10 videos. Built-in speaker and microphone facilitate operation and communication with guests, security of the building or other premises. Communication with another subscriber is also possible by receiving and sending text messages entered from the keyboard displayed on the screen. The door opening command from the icon on the screen can be additionally password protected. Optionally eight input lines can create a simple alarm system enriched with images from cameras. The subscriber is armed / disarmed by means of an icon on the screen. The alarm is signaled locally, on the security monitor and by PUSH notifications through mobile app. Disabling the alarm requires a special password.

| | |
|---|---|
| Device type | IP User Monitor |
| Display | LCD TFT |
| Resolution | 1024 x 600 px |
| Diagonal | 7" |
| Power supply input | 12 V DC |
| PoE | 48 V DC (802.3af) |
| Power consumption | 300mA |
| Additional functions | alarm functions, additional door panel, SD card slot, volume control, monitoring of the view from cameras, intercom calls, text messages, voice mail, photos and video recording, mobile application via WIFI |
| Dimensions | 210 x 140 x 20 mm |
| Operating temperature | from -10 to 55 °C |