

NOVUS

Bullet IP Camera with Motor-zoom Lens

NVIP-5H-4502M/F



FUNCTIONS



COMPLIANCE




KEY FEATURES

- Resolution: 5 MPX
- Lens: motorized, auto-focus function, f=2.7 ~ 13.5 mm/F1.8
- support for Chrome, Firefox, Opera, Safari browsers
- D/N function - IR cut filter
- Video content analysis based on Deep Learning
- Licence plate recognition (LPR)
- microSD card support
- WDR with double scan sensor
- two-way audio
- Min. illumination: 0.03 lx (0 lx, IR on)
- IR LED, range up to 45 m
- "Two way power" - when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

DIMENSIONS

The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the **DOWNLOADABLE FILES** tab.

| | |
|--|---|
| Image | |
| Image Sensor | 5 MPX CMOS sensor 1/2.7" OmniVision |
| Number of Effective Pixels | 2592 (H) x 1944 (V) |
| Min. Illumination | 0.03 lx/F1.2 - color mode, 0 lx (IR on) - B/W mode |
| Electronic Shutter | auto/manual: 1/5 s ~ 1/20000 s |
| Digital Slow Shutter (DSS) | up to 1/5 s |
| Wide Dynamic Range (WDR) | yes (double scan sensor), 120dB |
| Digital Noise Reduction (DNR) | 2D, 3D |
| Defog Function (F-DNR) | yes |
| Highlight Compensation (HLC) | yes |
| Reduction of image flicker (Antiflicker) | yes |
| Lens | |
| Lens Type | motorized, f=2.7 ~ 13.5 mm/F1.8 |
| Auto-focus | zoom trigger, manual trigger |
| DORI | |
| DORI (Detection, Observation, Recognition, Identification) | for f = 2.7mm - D: 56m, O: 22.4m, R: 11m, I: 5.6m for f = 13.7mm - D: 240m, O: 96m, R: 48m, I: 24m |
| Day/Night | |
| Switching Type | mechanical IR cut filter |
| Switching Mode | auto, manual, time |
| Switching Delay | 1 ~ 36 s |
| Visible Light Sensor | yes |
| Network | |
| Stream Resolution | 2592 x 1520, 2592 x 1944, 2304 x 1296, 1920 x 1080 (Full HD), 2048 x 1536 (QXGA), 1280 x 960, 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA) |
| Frame Rate | 30 fps for each resolution |
| Multistreaming Mode | number of streams: 3 |
| Video/Audio Compression | H.264, H.264+, H.265, H.265+/G.711 |
| Number of Simultaneous Connections | max. 10 |
| Bandwidth | 60 Mb/s in total |
| Network Protocols Support | HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, SMTP, P2P, HTML5 |
| Camera Configuration | from Internet Explorer, Firefox, Chrome, Opera, Safari browser languages: Polish, English, Russian, and others |
| Compatible Software | NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC |
| Mobile applications | RxCamView (iPhone, Android) |
| Video Analytics | |
| Functions | abandoned object, object disappearance, line cross, zone entrance, zone exit, multi loiter, cross counting, heat map, queue length detection, objects distinguishing, face recognition, comparing faces |
| Other functions | |
| Privacy Zones | 4 video mask type: single color |
| Motion Detection | yes |
| Audio Detection | yes |
| Image Processing | 180° image rotation, vertical flip, horizontal flip |
| Prealarm/Postalarm | up to 5 s/up to 30 s |
| System Reaction to Alarm Events | e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation, saving in the cloud storage |
| Restoring default settings | via web browser, using reset button |
| Licence plate recognition (LPR) | |
| Autonomous operation mode | yes - recognition function implemented in the camera |
| Capacity of License Plate Database | up to 10000 license plates, on all lists. |
| Types of recognized number plates | all countries of the European Union |
| Barrier control | yes - built-in relay output |
| Data recorded in the camera base | recognition date/time, number of recognised licence plate, image of recognised licence plate, presence on the "white list" or "black list" |
| Reactions for the licence plate recognition | e-mail with attachment, saving file on FTP server, alarm output activation |
| IR LED | |
| LED Number | 4 |
| Range | 45 m |
| Smart IR | yes (hardware support) |
| Interfaces | |
| Audio Input/Output | 1 x RCA/1 x RCA |
| Alarm Input/Output | 1 (NO/NC)/1 relay type (max. 12VDC/300mA) |
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s |
| Memory Card Slot | microSD - capacity up to 256GB |
| Installation parameters | |
| Dimensions (mm) | with bracket: 87 (W) x 83 (H) x 242 (L) |
| Weight | 0.82 kg |
| Degree of Protection | IP 66 (details in the user's manual) |



| | |
|-----------------------|-------------------------------------|
| Power Supply | 12 VDC, PoE (IEEE 802.3af, Class 3) |
| Surge protection | TVS 4000 V |
| Power Consumption | 2 W, 5 W (IR illuminator on) |
| Operating Temperature | -30°C – 55°C |
| Humidity | max. 95%, relative (non-condensing) |

A memory card is required for the face recognition and license plate recognition functions to work. The license plate recognition function is available for cameras with firmware V21.45.8.2.3_xxxx

