


## Bullet IP Camera with PIR detector

NVIP-2H-4231/PIR



### FUNCTIONS



The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

### COMPATIBILITY



### KEY FEATURES

- Resolution: 2 MPX
- Lens: fixed focal, f=2.8 mm/F2.2
- built-in microphone
- D/N function - IR cut filter
- reduction of false alarms - PIR detector
- microSD card support
- Min. Illumination: 0.1 lx (0 lx, IR on)
- IR LED, range up to 30 m
- "Two way power" - when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

### DIMENSIONS



<b>Image</b>	
Image Sensor	2 MPX CMOS sensor 1/2.7" SmartSens
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.1 lx/F1.2 - color mode, 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
<b>Lens</b>	
Lens Type	fixed focal, f=2.8 mm/F2.2
<b>Day/Night</b>	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Delay	1 ~ 36 s
Visible Light Sensor	yes
<b>Network</b>	
Stream Resolution	1920 x 1080 (Full HD), 640 x 480 (VGA)
Frame Rate	30 fps for 1920 x 1080 (Full HD), 20 fps for 640 x 480 (VGA)
Multistreaming Mode	2 streams
Video/Audio Compression	H.264, H.265/G.711
Number of Simultaneous Connections	max. 10
Bandwidth	40 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTPSP, RTP, UPnP, SMTP
Camera Configuration	from Internet Explorer browser languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC
<b>Other functions</b>	
Privacy Zones	4 video mask type: single color
Motion Detection	yes
PIR detector	range up to 7 m
Image Processing	180° image rotation, vertical flip, horizontal flip
Prealarm/Postalarm	up to 5 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, saving in the cloud storage
Restoring default settings	via web browser, using reset button
<b>IR LED</b>	
LED Number	2
Range	30 m
Smart IR	yes (hardware support)
<b>Interfaces</b>	
Audio Input/Output	built-in microphone
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
<b>Installation parameters</b>	
Dimensions (mm)	with bracket: 71 (Ø) x 150 (L)
Weight	0.4 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included, IK10 impact rating
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Surge protection	TVS 4000 V
Power Consumption	1.5 W, 4 W (IR illuminator on)
Operating Temperature	-30°C ~ 55°C
Humidity	max. 95% relative (non-condensing)