

NOVUS

Bullet IP Camera

NVIP-5H-4501

4000 VSS
IP



FUNCTIONS



COMPLIANCE



KEY FEATURES

- Resolution: 5 MPX
- Lens: fixed focal, f=2.8 mm/F1.6
- support for Chrome, Firefox, Opera, Safari browsers
- D/N function - IR cut filter
- Video content analysis based on Deep Learning
- Licence plate recognition (LPR)
- microSD card support
- WDR with double scan sensor
- Min. Illumination: 0.03 lx (0 lx, IR on)
- IR LED, range up to 30 m
- "Two way power" - when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

DIMENSIONS



The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

Image	
Image Sensor	5 MPX CMOS sensor 1/2.7" SmartSens
Number of Effective Pixels	2880 (H) x 1620 (V)
Min. Illumination	0.03 lx/F1.2 - color mode, 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s - 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
Lens	
Lens Type	fixed focal, f=2.8 mm/F1.6
DORI	
DORI (Detection, Observation, Recognition, Identification)	for f = 2.8mm - D: 56m, O: 22.4m, R: 11m, I: 5.6m
Day/Night	
Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Delay	1 ~ 36 s
Visible Light Sensor	yes
Network	
Stream Resolution	2880 x 1620, 2560 x 1440 (QHD), 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 640 x 480 (VGA), 320 x 240 (QVGA)
Frame Rate	30 fps for each resolution
Multistreaming Mode	number of streams: 3 (main stream, sub stream, third stream)
Video/Audio Compression	H.264, H.264+, H.265, H.265+/G.711
Number of Simultaneous Connections	max: 7 connections, (max. 20 streams in total)
Bandwidth	30 Mbit/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SMTP, P2P, HTML5
Camera Configuration	from Internet Explorer, Firefox, Chrome, Opera, Safari browser
Compatible Software	languages: Polish, English, Russian, and others
Mobile applications	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC RxCamView (iPhone, Android)
Video Analytics	
Functions	abandoned object, object disappearance, line cross, zone entrance, zone exit, zone violation, multi loiter, face detection, pedestrian detection, cross counting, heat map, queue length detection, objects distinguishing, vehicle detection, intrusion detection, smart motion detection with objects distinguishing
Other functions	
Privacy Zones	4 video mask type: single color
Motion Detection	yes
Region of interest (ROI)	8
Audio Detection	yes
Image Processing	180° image rotation, corridor mode, vertical flip, horizontal flip
Prealarm/Postalarm	up to 5 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, saving in the cloud storage, push notification
Restoring default settings	via web browser, using reset button
Licence plate recognition (LPR)	
Autonomous operation mode	yes - recognition function implemented in the camera
Capacity of License Plate Database	up to 10000 license plates, on all lists.
Types of recognized number plates	all countries of the European Union
Data recorded in the camera base	recognition date/time, number of recognised licence plate, image of recognised licence plate, presence on the "white list" or "black list"
Reactions for the licence plate recognition	e-mail with attachment, saving file on FTP server
IR LED	
LED Number	2
Range	30 m
Smart IR	yes (hardware support)
Interfaces	
Audio Input/Output	built-in microphone
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
Installation parameters	
Dimensions (mm)	with bracket: 71 (Ø) x 150 (L)
Weight	0.4 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included enclosure type: 4H-B
Power Supply	12 VDC, PoE (IEEE 802.3af, Klasa 3)
Surge protection	TVS 4000 V

Power Consumption	2 W. 4 W (IR illuminator on)
Operating Temperature	-30°C ~ 55°C
Humidity	max. 95%, relative (non-condensing)

A memory card is required for the license plate recognition function to work. License plate recognition and face detection functions are available for cameras with firmware V31.35.8.2.3_xxxx and newer.