




Vandal Proof IP Camera Starlight PRO DUO

NVIP-2VE-4231/WL



FUNCTIONS



The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the **DOWNLOADABLE FILES** tab.

COMPLIANCE



KEY FEATURES

- Resolution: 2 MPX
- Lens: fixed focal, f=3.6 mm/F1.0
- built-in microphone
- D/N function - IR cut filter
- microSD card support
- Min. illumination: 0.0005 lx (0 lx, IR on)
- IR LED, range up to 30 m
- white LED illuminator, range up to 25 m
- "Two way power" - when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

DIMENSIONS

Image	
Image Sensor	2 MPX CMOS sensor 1/2.7" SmartSens
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.0005 lx/F1.0 - color mode, 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s – 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
Lens	
Lens Type	fixed focal, f=3.6 mm/F1.0
Day/Night	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Delay	1 – 36 s
Switching Schedule	yes
Visible Light Sensor	yes
Network	
Stream Resolution	1920 x 1080 (Full HD), 640 x 480 (VGA)
Frame Rate	30 fps for, 20 fps for
Multistreaming Mode	number of streams: 2
Video/Audio Compression	H.264, H.265/G.711
Number of Simultaneous Connections	max. 10
Bandwidth	40 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, SMTP, P2P
ONVIF Protocol Support	Profile G/S
Camera Configuration	from Internet Explorer browser languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS
Mobile applications	RxCamView (iPhone, Android)
Other functions	
Privacy Zones	4 video mask type: single color
Motion Detection	yes
Image Processing	180° image rotation, vertical flip, horizontal flip
Prealarm/Postalarm	up to 5 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, saving in the cloud storage
Determent	white LEDs, steady/flashing light,
Restoring default settings	via web browser, using reset button
IR LED	
LED Number	2
Range	30 m
Smart IR	yes (hardware support)
White light illuminator	
LED Number	2, warm white color
Range	25 m
Smart Light	yes (hardware support)
Interfaces	
Audio Input/Output	built-in microphone
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
Installation parameters	
Dimensions (mm)	100 (Ø) x 90 (H)
Weight	0.42 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	vandalproof, aluminium, white
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Surge protection	TVS 4000 V
Power Consumption	1.2 W, 3.5 W (IR illuminator on), 3.3 W (white light illuminator on), 5.6 W (IR and white light illuminators on)
Operating Temperature	-30°C – 60°C
Humidity	max. 95% relative (non-condensing)

