



IP Entrance panel

NVE-EPV102P



KEY FEATURES:

- Number of users: 2
- Camera with 1920 x 1080 px resolution and 120° viewing angle, IR illumination
- Proximity card reader in the unique 125 kHz standard
- Mounting on an angle bracket with a rain cover
- Gate and door control function
- RTSP protocol support

The Villa NVE-EPV102P entrance panel is an elegant and aesthetic device designed for outdoor use, e.g. in front of the entrance to a property. It allows you to easily communicate with the homeowner using the call button and built-in color camera. Infrared (IR) backlighting allows for trouble-free use of the panel even at night. The built-in proximity card reader in the unique 125 kHz standard allows you to create simple access control and facilitates everyday use of the system. Support for two relays allows you to control both the gate and the door. The panel supports the RTSP protocol, making it possible to stream to Novus CCTV recorders. Image parameters, settings, and network protocols can be configured from the web application client.

Included:

- IP Entrance panel
- wall bracket
- 2x fixing screws and expansion bolts
- inner hexagon screw
- allen wrench
- 3x proximity tag
- RJ45 adapter
- nameplate sticker
- thimble
- short manual

| | |
|----------------------------|---|
| Device type | IP Entrance panel |
| Number of users | 2 |
| Sensor | CMOS HD 2 MPx |
| Resolution | 1920 x 1080 px |
| View angle | 120 ° |
| Video coding | H.265 (default); H.264 |
| Power supply input | 15 V DC |
| PoE | 48 V DC (802.3af) |
| Power consumption | 300mA 4,5 W (Max.) |
| Lock output | NO Relay (4 A / 36 V DC/AC) |
| Gate output | NO Relay (4 A / 36 V DC/AC) |
| Exit Button | No |
| Door open status indicator | No |
| Port LAN | 1 x 10M / 100M Ethernet |
| Wi-Fi | No |
| Standalone mode | No |
| Card reader format | unique standard |
| Number of cards supported | 100 |
| Numeric keyboard | No |
| Access Code | No |
| Additional functions | LED IR, mounting on an angular bracket, Status LEDs |
| Dimensions | 154 x 55 x 21 mm |
| Weight | 380g |
| Protection code | IP66 |
| IK Rating | IK07 |
| Operating temperature | from -40 to 60 °C |
| Color | Graphite black (RAL9011) |