



## Vandal Proof AHD Multistandard Camera

NHDC-2VE-6302-II



### FUNCTIONS



**NOTICE: Analogue video standard CVBS is not supported.**

### COMPLIANCE



### KEY FEATURES

- D/N function - IR cut filter
- resolution 1080p
- Lens: varifocal, f=2.8 ~ 12 mm/F1.2
- Smart IR function
- Min. Illumination: 0.005 lx (0 lx, IR on)
- IR LED, range up to 50 m

### DIMENSIONS



<b>Image</b>	
Image Sensor	CMOS sensor 1/2.8" SMARTSENS
Operating mode	AHD 1080p, TVI 1080p, CVI 1080p
Number of Effective Pixels	1920 (H) x 1088 (V)
Resolution	1080p
Min. Illumination	0.005 lx/F1.2 - color mode, 0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/50 s ~ 1/100000 s
High Light Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D
<b>Lens</b>	
Lens Type	varifocal, f=2.8 ~ 12 mm/F1.2
<b>Day/Night</b>	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual
Visible Light Sensor	yes
<b>Other functions</b>	
OSD	languages: English, others
Image Processing	Defective Pixel Correction (DPC), sharpening
Remote control	Yes (COAX protocol)
<b>IR LED</b>	
LED Number	3
Range	50 m
Smart IR	yes (software support)
<b>Interfaces</b>	
Video Output	BNC, 1.0 Vp-p, 75 Ohm
<b>Installation parameters</b>	
Dimensions (mm)	112 (Ø) x 100 (H)
Weight	0.6 kg
Degree of Protection	IP 67 (details in the user's manual)
Enclosure	vandalproof, aluminium, white enclosure type: 6VE-M
Power Supply	12 VDC
Power Consumption	1 W, 4 W (IR illuminator on)
Operating Temperature	-30°C ~ 50°C
Humidity	max. 90%, relative (non-condensing)

\* Note: UTC functionality available on cameras with serial numbers starting from: 150611xxxx  
Remote controller type: NV-RCUTC-35HD