


Multistandard AHD Recorder

NHDR-6004A-H1-II



FUNCTIONS




COMPLIANCE



KEY FEATURES

- Video channels: 4, audio channels: 1
- Recording speed: up to 120 fps (AHD), up to 60 fps (IP)
- Internal HDDs mount: up to 1
- Monitor outputs: 3 (2 x main, 1 x spot)
- Supports HD analog cameras (720p, 1080p, 4MPX, 5MPX)
- Supports AHD, TVI, CVI cameras
- IP cameras support (hybrid mode)
- Intelligent image analysis

DIMENSIONS



| | |
|--|---|
| Video | |
| Video Input | 4 x BNC |
| Operating mode | AHD 5Mpx, TVI 5Mpx, CVI 5Mpx, analog 960H |
| Monitor Output | main (split screen, full screen, sequence): 1 x HDMI (FullHD), 1 x VGA (FullHD), 1 x BNC, spot: 1 x BNC interchangeably to main output (only analog cameras for spot display) |
| IP Streams | hybrid mode: 4 x BNC + 2 x IP IP mode: 0 x BNC + 6 x IP |
| Supported IP resolution | max. 2592 x 1944 |
| Audio | |
| Audio Input/Output | 1 x RCA (Line-in)/1 x HDMI, 1 x RCA |
| Recording | |
| Compression | H.264, H.265, H.265+ |
| Recording Speed | 120 fps (1280 x 720 - HD) 120 fps (960 x 1080 - 1080p Lite) 60 fps (1920 x 1080 - FullHD) 60 fps (1280 x 1440 - 4Mpx Lite) 40 fps (1280 x 1944 - 5Mpx Lite) |
| IP recording speed | hybrid mode: 60fps IP mode: 180fps |
| IP stream size | hybrid mode: 16 Mb/s in total from all IP cameras IP mode: 32 Mb/s in total from all IP cameras |
| Recording Mode | continuous, triggered by: REC/PANIC button, alarm input, motion detection, image analysis |
| Schedule | individual settings for: each camera, each day of the week, configuration with an accuracy of: 1 min, possibility of combining individual recording modes |
| Prealarm/postalarm | up to 5 s (up to 10 min) |
| Playback | |
| Playback speed | 120 fps |
| IP playback speed | 60 fps |
| Recorded Data Search | by date/time, events, image analysis events, motion in a defined area, tags |
| Backup | |
| Backup Methods | USB port (HDD or Flash memory), network |
| Backup File Format | AVI, RPAS (player included) |
| Storage | |
| Internal storage | available mount: 1 x HDD 3.5" SATA |
| Total Internal Capacity | 10 TB |
| Alarm | |
| IP Camera Alarm Input/Output | supports IP camera's alarm input/output |
| Motion Detection | 18 x 22 grid, individual settings of sensitivity |
| System Reaction to Alarm Events | buzzer, e-mail, alarm output activation, recording activation, PTZ, Full Screen |
| Intelligent image analysis | |
| Number of channels | 4 x BNC, 2 x IP (6000 Serie) |
| Supported functions for analog cameras | Line cross, Zone entrance, Smart Motion Detection |
| Supported functions for IP cameras | Object detection, Exception, Scene change, Video blurred, Video color cast, Line cross, Zone entrance, Abandoned object, Object disappearance |
| Network | |
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s |
| Network Protocols Support | HTTP, TCP/IP, IPv4/IPv6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, IEEE 802.1X, PPPoE, SMTP, P2P, POS, HTML5 |
| PC/MAC Software | NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 |
| Mobile applications | SuperLive Plus (iPhone, Android) |
| Number of Simultaneous Connections | up to 5 (live monitoring); 5, playback: 5, configuration: 5), live monitoring up to 10 mainstreams, 24 substreams, playback up to 5 streams |
| Bandwidth | 40 Mb/s in total to all client workstations |
| PTZ | |
| PTZ Ports | 1 x RS-485 |
| PTZ Protocols | Pelco-D, Pelco-P |
| PTZ Functions | pan/tilt/zoom, preset commands, patterns |
| COAX | |
| COAX Functions | menu, zoom, focus, PTZ |
| Auxiliary Interfaces | |
| USB Ports | 2 x USB 2.0 |
| Operating system | |
| Operating System | Linux |
| OSD | languages: Polish, English, Russian, others |
| Control | IR remote controller, PC mouse (in-set included), network |
| System Diagnostic | automatic control of: HDDs, camera connection loss |
| Security | password protection, IP filtering, MAC filtering |
| Installation parameters | |
| Dimensions (mm) | 255 (W) x 42 (H) x 233 (D) |
| Weight | 0.77 kg (without HDD) |
| Power Supply | 12 VDC (100 - 240 VAC/12 VDC PSU in-set included) |
| Power Consumption | 20 W (with 1 HDD) |
| Operating Temperature | -10°C - 50°C |

The recorder is dedicated to work with AHD cameras, Novus 6000 series IP cameras and achieves the best functionality with them. In case of work with IP cameras intelligent image analysis, dualstream mode, PTZ control, motion detection and alarm inputs / outputs functions depend on the functionality of the IP camera and the capabilities of the communication protocol. Detailed data on camera compatibility with recorders and compatible hard drives can be found in the compatibility tables available in the DOWNLOADABLE FILES tab. Display and playback speeds are achieved using dual stream. The recording speed of analog cameras may be limited during playback.