




# 4 MPX IP camera with Deep Learning-based image analysis and active deterrence

NVIP-4VE-4231/WLAD



4000 VSS IP

## FUNCTIONS



The camera is dedicated to work with NOVUS 4000 series recorders. Detailed data can be found in the compatibility table available in the **DOWNLOADABLE FILES** tab.

## COMPLIANCE



## KEY FEATURES

- Resolution: 4 MPX
- Lens: fixed focal, f=2.8 mm/F1.0
- active deterrence
- D/N function - IR cut filter
- Video content analysis based on Deep Learning
- microSD card support
- two-way audio
- Min. Illumination: 0.0005 lx (0 lx, IR on)
- IR LED, range up to 25 m
- white LED illuminator, range up to 20 m
- "Two way power" - when connected to a PoE switch, it allows to power the low power receiver from the camera's power socket

## DIMENSIONS

Image	
Image Sensor	4 MPX CMOS sensor 1/3" SmartSens
Number of Effective Pixels	2560 (H) x 1440 (V)
Min. Illumination	0.0005 lx/F1.0 - color mode, 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/5 s ~ 1/20000 s
Digital Slow Shutter (DSS)	up to 1/5 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
Lens	
Lens Type	fixed focal, f=2.8 mm/F1.0
DORI	
DORI (Detection, Observation, Recognition, Identification)	for f = 2.8mm - D: 56m, O: 22.4m, R: 11m, I: 5.6m
Day/Night	
Mode	day/night switching: mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Delay	1 ~ 36 s
Network	
Stream Resolution	2560 x 1440 (QHD), 640 x 480 (VGA)
Frame Rate	25 fps for each resolution
Multistreaming Mode	number of streams: 2
Video/Audio Compression	H.264, H.265/G.711
Number of Simultaneous Connections	max. 3 connections, (max. 10 streams in total)
Bandwidth	15 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, HTTPS, DHCP, DNS, DDNS, NTP, RTSP, RTP, SMTP, P2P
Camera Configuration	from Internet Explorer browser languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC
Mobile applications	RxCamView (iPhone, Android)
Video Analytics	
Functions	line cross, zone entrance, zone exit, zone violation, objects distinguishing, intrusion detection, smart motion detection with objects distinguishing
Other functions	
Privacy Zones	4 video mask type: single color
Motion Detection	yes
Audio Detection	yes
Image Processing	180° image rotation, vertical flip, horizontal flip
Prealarm/Postalarm	up to 5 s/up to 30 s
System Reaction to Alarm Events	e-mail with attachment, saving file on SD card, active deterrent functions
Determent	white LEDs, steady/flashing light, red and blue LEDs, flashing light, audio signaling device (siren)
Restoring default settings	via web browser, using reset button
IR LED	
LED Number	1
Range	25 m
Smart IR	yes (hardware support)
White light illuminator	
LED Number	2, warm white color
Range	20 m
Smart Light	yes (hardware support)
Interfaces	
Audio Input/Output	built-in microphone/speaker
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
Installation parameters	
Dimensions (mm)	100 (Φ) x 90 (H)
Weight	0.43 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	vandalproof, aluminium, white enclosure type: 4VE-S



90 mm

100 mm (Ø)



Power Supply	12 VDC, PoE (IEEE 802.3af, Klasa 3)
Surge protection	TVS 4000 V
Power Consumption	1.5 W, 3 W (IR illuminator on), 5.5 W (white light illuminator on), 6.5 W (active deterrence functions enabled)
Operating Temperature	-35°C ~ 60°C
Humidity	max. 95%, relative (non-condensing)