

Vandal Proof AHD Camera

NVAHD-1DN5101V/IR-1



5000
AHD SERIES

FUNCTIONS



KEY FEATURES

- D/N function - IR cut filter
- resolution 720p
- Lens: fixed focal, f=3.6 mm/F2.0
- optional UTC remote controller
- Min. Illumination from 0.0001 lx (0 lx, IR on)
- IR LED, range up to 15 m

DIMENSIONS



Image	
Image Sensor	CMOS sensor 1/3" SONY
Operating mode	AHD 720p, analog 960H
Number of Effective Pixels	1280 (H) x 1024 (V)
Resolution	720p
Min. Illumination	0.5 lx/F2.0 - color mode, 0.01 lx/F2.0 - B/W mode, 0.001 lx/F2.0 - color mode (DSS), 0.0001 lx/F2.0 - B/W mode (DSS), 0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s (AHD), 1/50 s ~ 1/50000 s (analog 960H)
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Lens	
Lens Type	fixed focal, f=3.6 mm/F2.0
Day/Night	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 60 s
Visible Light Sensor	yes
Other functions	
OSD	languages: Polish, English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Remote control	Yes (optional UTC remote control)*
IR LED	
LED Number	24
Range	15 m
Angle	80°
Interfaces	
Video Output	BNC, 1.0 Vp-p, 75 Ohm
Installation parameters	
Dimensions (mm)	93 (Ø) x 75 (H)
Weight	0.33 kg
Degree of Protection	IP 65 (details in the user's manual)
Enclosure	vandalproof, aluminium, ivory
Power Supply	12 VDC
Power Consumption	1.2 W, 3.2 W (IR illuminator on)
Operating Temperature	-30°C ~ 40°C

* Note: UTC functionality available on cameras with serial numbers starting from: 150611xxxx
Remote controller type: NV-RCUTC-35HD