# 32'' LCD monitor designed for continuous operation

NVM-6032LCD



## FUNCTIONS

NDAA · 8 ms · 32" · IPS · 24/7

## KEY FEATURES

- dedicated to continuous operation (24/7)
- anti-glare panel coating eliminating reflections
- short response time (8ms) preventing blurring of dynamic image parts
- image correction options to help you capture all the details even in difficult lighting conditions
- LED backlight

## DIMENSIONS




| | |
|---|---|
| **LCD PANEL** | |
| Panel Type | IPS, LED backlight |
| Surface treatment | Anti-glare treatment (haze 25%), 3H hard coating |
| Screen Size (Diagonal) | 32" |
| Panel Resolution | 1920 x 1080 |
| Viewable area | 698.4 x 392.85 mm |
| Pixel pitch | 0.36375 mm |
| Format | 16:9 |
| Brightness | 350 cd/m2 |
| Contrast Ratio | 1000:1 |
| Viewing Angle (H/V) | 178°/178° |
| Response Time | 8 ms |
| Refresh frequency | 60 Hz (max) |
| Display Color | 16.7 mln (gamut: sRGB: 92%, DCI-P3: 74%) |
| **Other functions** | |
| OSD | languages: Polish, English |
| Digital Filter | 3D |
| Built-in Speakers | 2 x 3 W |
| **Interfaces** | |
| Video Input | 2 x CVBS, BNC connector (loop-through), 1 x VGA, 1 x HDMI |
| Audio Input | 1 x Mini Jack stereo, 1 x HDMI (stereo) |
| External Control | Infrared remote control |
| Other Connectivity | USB 2.0 (for service) |
| **Installation parameters** | |
| Dimensions (mm) | 738 (W) x 478 (H) x 190 (D) |
| Weight | 4 kg |
| Case | black, plastic |
| Power Supply | 100 ~ 240 VAC |
| Power Consumption | 35 W (max)<br>0.3 W (in standby mode) |
| Operating Temperature | +10°C ~ +45°C |
| Humidity | 15% - 85%, relative (non-condensing) |
| Mounting Standard | VESA 100 x 100 mm |